Homax

Wall Texture

Textura para pared

PRO GRADE

ORANGE PEEL

Cáscara de naranja

Fine • 125 sq. ft.

Medium • 85 sq. ft.

Heavy • 70 sq. ft.

HOPPER GUN CONTROL™

Pressure & Spray Tip Adjustment

Delivers an Invisible Repair
No Prime, Lower Odor Formula
Dries in 5 Minutes

Ajuste en la Pistola de Presión y Pulverización
Brinda una Reparación Invisible
Fórmula con menos Olor, Sin Imprimar
Se seca en 5 Minutos

DANGER! FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
Read other cautions on side/back panel before using.

¡PELIGRO! LÍQUIDO Y VAPOR INFLAMABLE. DAÑINO O FATAL EN CASO DE INGESTIÓN. CONTENIDO BAJO PRESIÓN. CAUSA IRRITACIÓN DE LOS OJOS, LA PIEL Y LAS VÍAS RESPIRATORIAS. Lea otras precauciones en el panel posterior y laterales antes de usar.

NET WT 25 OZ (709 g)

OIL BASED BASE DE ACEITE

Homax® Pro Grade Wall Texture with Dual Control™ technology is the latest innovation in aerosol textures. This professional tool features adjustment of both pressure and pattern —similar to that of a gun and hopper. The oil-based Pro formula provides the same ultra-fast dry results as the original, but now with an advanced lower odor and no prime formulation. This time-saving tool provides portable and convenient delivery of a full range of texture patterns to achieve an invisible repair.

Visit us at www.homax.com or scan this code to watch a How-to Video

Text of Video to play on Smartphone or explore one on Smartphone pour voir vidéo.

READ AND FOLLOW ALL WARNINGS AND PRECAUTIONS. PROTECT SURROUNDING AREA FROM OVERSPRAY. DO NOT SPRAY ON CLOTHING, FURNITURE OR CARPET.

DIRECTIONS FOR USE: MAKE NECESSARY WALL REPAIRS BEFORE APPLYING. SPOT PRIME REPAIR AREA BEFORE TEXTURE APPLICATION TO ENSURE BEST RESULTS. Priming after texture application is no longer needed. Always practice spraying on cardboard or scrap drywall to determine finished pattern.

1. SHAKE CAN upside-down vigorously for one full minute before using and continue subtly during use.
2. REMOVE safety tab from top of trigger. REMOVE red clip from tube position toggle. RETAIN red clip and mustach for storage.
3. ADJUST PATTERN
   POINTING AWAY FROM FACE, TURN YELLOW SPRAY TIP TO DESIRED PATTERN. CASCADE for FINE. COARSER CASCADE for HEAVY
4. ADJUST PRESSURE*
   MOVE YELLOW TOGGLE:
   ADJUST for HIGH, LEFT for LOW
   *As contents are dispensed or can thickness, adjust pressure and pattern to maintain consistent texture appearance.
5. SPRAY at a distance of 18"-24" from wall using a circular (not sweeping) motion. Note: Depending upon PRESSURE & PATTERN settings, distance may vary. Spray best between 65-90°F. Apply in medium pattern, covering only 50% of surface. Shake can occasionally throughout use.
   DRY TIME: Allow to dry 5-30 minutes before painting. Heavier textures may require longer dry time, depending upon temperature and humidity.
   CLEAN-UP: Acetone, lacquer thinner, or isopropyl alcohol.
6. AFTER USE/TO STORE: Clear nozzle by turning can upside down, move toggle to high pressure and spray until texture is cleared. Replace red clip under pressure toggle for storage.
7. PAINT with 2 coats or more for complete hide and to match glaze (dependent upon color and paint manufacturer's instructions).

DANGER! Contains Nepheline Syenite, Diacetone Alcohol, Ethanol, Wollastonite, Titanium Dioxide and Propane/Isobutane blend (propellant). FLAMMABLE. Vapors may cause flash fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. May cause dizziness, headache or nausea. Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles and gloves. An appropriate and properly fitted NIOSH approved respirator may provide extra protection, but should only be used in accordance with manufacturer's directions for respirator use. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. CONTENTS UNDER PRESSURE. Do not puncture or incinerate (burn) container. Do not expose to heat or store at temperatures above 120°F. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention. KEEP OUT OF REACH OF CHILDREN. WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm. WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LEER Y ACATAR TODAS LAS ADVERTENCIAS Y PRECAUCIONES. PROTEGER LAS ÁREAS CERCANAS DE LA NEBLINA DE PULVERIZACIÓN. NO PULVERICE SOBRE PRENDAS DE VESTIR, MUEBLES O ALFOMBRAS.

INSTRUCCIONES DE EMPLEO: HACER TODAS LAS REPARACIONES EN LAS PAREDES QUE SEAN NECESARIAS. ANTES DE APLICAR EL PRODUCTO, CONTINUAR LA ZONA A REPARAR ANTES DE APLICAR LA TEXTURA PARA ASEGURARSE MEJORES RESULTADOS. La imprimación después de la aplicación de la textura ya no es necesaria. Siempre practique pulverizar sobre cartón o sobre un trozo de panel de yeso para determinar el acabado que prefiere.

1. AGITAR LA LATA al revés vigorosamente por un minuto completo y continúe suavemente durante el uso.
2. RETIRAR la lengüeta de seguridad de la parte superior del gatillo. RETIRAR el clip rojo de la parte inferior de la boca de presión. RETENER el clip rojo y el mostacho para su almacenamiento.
3. AJUSTAR EL MODELO
   APUNTANDO LEJOS DE LA CARA, GIRAR EL CON AMARILLO PARA EL MODELO DESEADO:
   GIR EL CONTRAPUNTEO AMARIL DEL ROCÍO para ROCÍO, GIR EL CONTRAPUNTEO PARA LAS ARÁNDANOS DEL ROCÍO para ARÁNDANOS
4. AJUSTAR LA PRESIÓN*
   MOVER LA LENGÜETA AMARILLA:
   AJUSTAR para ALTO, IZQUIERDA para BAJO
   *Cuando pulsar del contenido dispensado, ajuste la presión y el modelo para mantener una apariencia de la textura consistente.
5. PULVERIZAR a una distancia de 45 a 61 cm (18" a 24") de la pared haciendo un movimiento circular (no de barrido). Nota: Dependiendo de los ajustes de PRESIÓN y MODELO, la distancia puede variar. La pulverización es mejor entre 18 a 30°C (65 a 90°F). Aplicar en forma delgada, cubriendo solamente el 50% de la superficie. Agitar la lata ocasionalmente durante su uso.
   TIEMPO DE SECADO: Espere de 5 a 30 minutos a que se seque antes de pintar. Las texturas más pesadas pueden requerir un tiempo de secado más prolongado, dependiendo de la temperatura y humedad.
   LIMPIEZA: Acetona, diluyente para laca o alcohol isopropílico.
6. DESPUÉS DE USAR PARA ALMACENAR
   Destapar la boquilla girando la lata hacia abajo, mover la lengüeta a la posición de alta presión y pulverizar hasta que no quede textura.
7. PINTAR 2 capas de pintura o más para un cubrimiento total y para que coincida con la glaseado (dependiendo del color y de las instrucciones del fabricante de pintura).

¡PELIGRO! Los vapores pueden provocar fogonazos. Mantener alejado del calor, chispas y llamas. Extinguir todas las llamas y fuentes de ignición durante su uso y hasta que se hayan dispersado todos los vapores. Evitar la acumulación de vapores abriendo todas las ventanas y puertas para obtener ventilación cruzada. Puede provocar mareos, cefaleas o náuseas. Utilizar solamente con ventilación adecuada. Evite aspirar el vapor y la bruma de la pulverización. Evite el contacto con los ojos y la piel. Utilizar gafas protectoras o gafas y guantes de seguridad. Un respirador adecuado y debidamente colocado aprobado por el NIOSH puede brindar protección adicional, pero se debe utilizar solamente de acuerdo con las instrucciones del fabricante para el uso del respirador. No perforar o incinerar (quemar) el envase. No exponer al calor o a temperaturas superiores a 49°C (120°F). Evitar la exposición prolongada al sol o al calor de radiadores, estufas, agua caliente u otras fuentes de calor que puedan provocar estallidos.

Flat Paint Product VOC < 50% PWM III <1.30
Pounds Pending.

MANUFACTURED A Premier Brand of THE HOMAX GROUP, INC.
Bellingham WA 98227
www.homaxproducts.com
800-729-8829

MADE IN USA

0000_XXXXX_000000

4 10720 04555 1